ASAP POS

ZW861

80mmThermal Receipt Printer

Wall printing | Two dimensional code printing | Automatic paper cutting | Big font

High speed printing | Queue function

Features

1. Modern craft design, fashionable, minimalist, compact and exquisite
2. High-speed printing up to 260mm/s and 2MB memory
3. Flexible interface, equipped with LED indicator light, machine status is clear at a glance
4. Two paper output methods are adjustable, "top paper output" and "front paper output" to achieve multi-angle printing
5. Multi-function sensor, capable of over-temperature detection, paper out detection and cover opening detection





Model	ZW861
Print Method	Direct Thermal
Resolution	203dpi
Printing Width	80mm(MAX)/72mm(default)
Paper separator (option)	58mm(57.5±0.5mm) 80mm(79.5±0.5mm)
Memory	Input buffer: 2M NV Flash: 256kbytes
Interface	USB+LAN/USB+LAN+WIFI/BLUETOOTH(optional)
Print Speed	260mm/s
Discharge direction	"Top paper"and"Front paper"can be adjusted in both directions

Fonts	
Font A	12x24
Font B	9x17
Chinese	GB18030, BIG5 24x24dots
Japanese/Korea	Japanese JIS、Korean KSC5601(optional)
User-defined	Support
Character Size (mm)	Font A:1.5x3.0mm;Font B:1.1x2.1mm;Simple/ Trinditional:3.0x3.0mm

Barcode	
1D	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/ CODE39/ITF/CODABAR/CODE93/CODE128
2D	QR code,PDF417

Detection	
Sensors	Lack of paper detection,open cover detection, overtemperature detection
Colour	All Black,White gold,Black gold(default)

Power Supply	
Input	AC 100V-240V 50/60HZ
Output	DC 24V/2.5A

Paper	
Paper Type	Thermal Receipt Paper
Paper Width	58mm(57.5±0.5mm)/80mm(79.5±0.5mm)
Paper Thickness	0.04~0.08mm
Roll Dia	Max. Ø 82 mm
Paper Load	Easy paper loading
Paper Cut	Auto-cutter(half cut)

Physical Charateristics	
Working Condition	5°C~45°C, 10%~90%RH
Storage Condition	-20°C-60°C,10%~90%RH
Dimensions	129(D)x128(W)x131.6(H)mm
Net weight	Net weight: 1.0kg Gross weight: 1.7kg

Reliability	
Printing head	150KM
Cutter	2.0million

Accessories	
Accessories	USB data cable,Power adaptor,Power cord, Paper roll,CD,Manual,Paper separator,Serial cable(optional)

Packing	
Individual box	Dimension 230×155×144mm(L×W×H) 1unit/carton
Master carton	Dimension 480×310×490mm(L×W×H) 12unit/carton

OS	
Emulation	ESC/POS
Driver	Windows/Linux/Mac
SDK	Android/ iOS/Windows
Safety standard	CCC/ROHS/CE